

K-Sun LABELShop® GREEN MACHINE® FEATURES



Machine Dimensions	7.1"/180mm (W) x 9.3"/236mm (D) x 3.2"/81mm (H)
Machine Weight	1.7 Lbs. /.77Kg (excluding batteries and tape cartridge)
Print Resolution	180 dpi
Barcode Formats	6 barcode formats: Code 39, Code 128, ITF, UPC-A, UPC-E, and CODABAR for custom barcode creation
LCD	Backlit LCD Display: 4 lines, 11 Settings for optimum viewing conditions
Characters	Fonts: 14 Symbols: 464 general symbols, 373 pictographs, 87 frames, 4 tables Language Prompts: Provides operational instructions for domestic and international labeling in: English, Spanish, French, Italian, German, Danish, Norwegian, Swedish, Finnish, Russian, Croatian, and Greek 7 Font Point Sizes: 6,10,13,19,26,38,48 Background Designs: Wave, diamonds, cherry, card, arabesque, mesh, or dots for special effects Text Size and Font Style Hot Keys: For easy selection of type sizes and font styles Euro-Latin Hot Key: Allows instant access to 79 European and Latin characters for multiple language labels
Tape Cutter	PeelGuard® Tape Trimmer: Exclusive built-in electronic cutting system rounds label corners on demand Provides edge peel protection for more permanent labels Rounded corners make more professional looking labels
Tape Colors	60 Combinations (size, color, and shrink combinations)
Memory Storage	Holds 99 Files/5,000 characters for safe storage of common labels
Formatting	multi-line
Label Length	72 inches, 6 feet, 1.8 meters
Tape and Heat Shrink Tube Supplies	Two-In-One Tape: • Flexible Polyester Base for Wire and Cable Wrap.

- Polyester Provides Durability and Permanent Adhesive
 - Strength for Flat Surfaces Too.
 - Solves Two Requirements With One Tape.
- Tape Width Selection: 5-Widths- 1/6"(4mm), 1/4"(6mm), 3/8"(9mm), 1/2"(12mm), 3/4"(18mm)
 Heat Shrink Tube Selection: Polyolefin Heat Shrink Tube Material in 1/8" and 3/16" Widths, Three Color Combinations

Environmental and Safety

- Printer and AC Adapter are compliant with Eco-Design Directives
- Does not produce Ozone, ionizing or UV radiation or other types of radiation
- Non-PVC, lead-free parts, and no mercury
- Flash Memory Backup System: No toxic batteries to cause waste disposal problems
- RoHS/WEEE compliant (no hazardous materials used)
- International AC Adapter: Meets/exceeds CE,UL,cUL,LPS,TUV and GS compliance, certification, and testing standards
- AC Adapter meets/exceeds Energy Star and California Energy Code V no-load energy reduction and efficiency standards
- Halogen-free adhesive labeling tape supplies
- Battery cover made from recycled plastic
- Recycled paper used in all packaging and printed instructions
- Tape cartridges have 50% recycled plastic and are recyclable through K-Sun
- Printer Auto Shut-off after 5 minutes saves energy

Cable Label Function

Cable Label "Quick Key" Speeds Design of Wire and Cable Labels

Power

Runs on Batteries- 6AA, Universal International AC Adapter (100-240V) switching power adapter included with The GREEN MACHINE® meets and exceeds EU, UK, CSA, UL, CE and Level V California energy reduction standards and is available in multiple plug configurations for U.S. and international electrical requirements

Print Technology

High Durability Thermal Transfer

Tape Sizes

1/6", 1/4", 3/8", 1/2" and 3/4"

Shrink Tube Sizes

5 Heat Shrink Tube Sizes: 1/8", 3/16", 1/4", 3/8", and 1/2"